Celanese
The chemistry inside innovation™

Zytel® PLS95G50DH2 BK261

ZYTEL® PLUS & XT NYLON RESIN

Common features of Zytel® nylon resin include mechanical and physical properties such as high mechanical strength, excellent balance of stiffness and toughness, good high temperature performance, good electrical and flammability properties, good abrasion and chemical resistance. In addition, Zytel® nylon resins are available in different modified and reinforced grades to create a wide range of products with tailored properties for specific processes and end-uses. Zytel® nylon resin, including most flame retardant grades, offer the ability to be coloured.

The good melt stability of Zytel® nylon resin normally enables the recycling of properly handled production waste. If recycling is not possible, we recommend, as the preferred option, incineration with energy recovery (-31kJ/g of base polymer) in appropriately equipped installations. For disposal, local regulations have to be observed.

Zytel® nylon resin typically is used in demanding applications in the automotive, furniture, domestic appliances, sporting goods and construction industry.

Zytel® PLS95G50DH2 BK261 is a high flow 50% glass reinforced PA nylon resin using our SHIELD Technology, providing exceptional Heat Resistance & High stiffness for automotive under hood applications like charge air cooler caps.

Product information

Resin Identification	PA66/6T-GF50	ISO 1043
Part Marking Code	>PA66/6T-GF50<	ISO 11469
ISO designation	ISO 16396-PA66/6T,GF50,M1CGHR,S12-160	

Rheological properties

	dry/cond.		
Viscosity number	3460[1]/*	in³/lb	ISO 307, 1628
Molding shrinkage, parallel	0.3 / -	%	ISO 294-4, 2577
Molding shrinkage, normal	0.6 / -	%	ISO 294-4, 2577

[1]: sulphuric acid 96%

Typical mechanical properties

	dry/cond.		
Tensile modulus	2.47E6 / 1.74E6	psi	ISO 527-1/-2
Tensile stress at break, 5mm/min	34800 / 24700	psi	ISO 527-1/-2
Tensile strain at break, 5mm/min	2.6 / 4	%	ISO 527-1/-2
Flexural modulus	2.32E6 / -	psi	ISO 178
Flexural strength	53700 / -	psi	ISO 178
Tensile creep modulus, 1h	* / 1.45E6	psi	ISO 899-1
Tensile creep modulus, 1000h	* / 943000	psi	ISO 899-1
Charpy impact strength, 23°C	42.8 / 45.2	ftlb/in²	ISO 179/1eU
Charpy impact strength, -30°C	38.1 / 38.1	ftlb/in²	ISO 179/1eU
Charpy notched impact strength, 23°C	7.14 / 9.51	ftlb/in²	ISO 179/1eA
Charpy notched impact strength, -30°C	7.61 / -	ftlb/in²	ISO 179/1eA

Thermal properties

	dry/cond.		
Melting temperature, 10°C/min	513 / *	°F	ISO 11357-1/-3
Glass transition temperature, 10°C/min	149 / -	°F	ISO 11357-1/-3
Temperature of deflection under load, 1.8 MPa	489 / *	°F	ISO 75-1/-2
Temperature of deflection under load, 0.45 MPa	505 / *	°F	ISO 75-1/-2
Coefficient of linear thermal expansion (CLTE), parallel	0.08 / *	E-4/°F	ISO 11359-1/-2

Zytel® PLS95G50DH2 BK261

ZYTEL® PLUS & XT NYLON RESIN

Coefficient of linear thermal expansion (CLTE), parallel, -40-23°C	0.0833 / *	E-4/°F	ISO 11359-1/-2
Coefficient of linear thermal expansion (CLTE), parallel, 55-160°C	0.0278 / *	E-4/°F	ISO 11359-1/-2
Coefficient of linear thermal expansion (CLTE), normal	0.372 / *	E-4/°F	ISO 11359-1/-2
Coefficient of linear thermal expansion (CLTE), normal, -40-23°C	0.311 / *	E-4/°F	ISO 11359-1/-2
Coefficient of linear thermal expansion (CLTE), normal, 55-160°C	0.667 / *	E-4/°F	ISO 11359-1/-2

Flammability

	dry/cond.		
Burning Behav. at 1.5mm nom. thickn.	HB / *	class	IEC 60695-11-10
Thickness tested	0.0591 / *	in	IEC 60695-11-10
FMVSS Class	B		ISO 3795 (FMVSS 302)
Burning rate, Thickness 1 mm	1.69	in/min	ISO 3795 (FMVSS 302)

Physical/Other properties

	dry/cond.		
Humidity absorption, 2mm	1.3 / *	%	Sim. to ISO 62
Water absorption, 2mm	4.5 / *	%	Sim. to ISO 62
Density	0.0574 / -	lb/in³	ISO 1183

Injection

Drying Recommended	yes	
Drying Temperature	176	°F
Drying Time, Dehumidified Dryer	2 - 4	h
Processing Moisture Content	≤0.2	%
Melt Temperature Optimum	554	°F
Min. melt temperature	536	°F
Max. melt temperature	572	°F
Max. screw tangential speed	≤0.2	m/s
Mold Temperature Optimum	203	°F
Min. mold temperature	158	°F
Max. mold temperature	248	°F
Hold pressure range	7250 - 14500	psi
Hold pressure time	0.0762	s/mil
Hold Pressure Time (h is the max. wall thickness of the part in mm)	h^2+2	s
Ejection temperature	424	°F

Automotive

OEM	STANDARD	ADDITIONAL INFORMATION
General Motors	GMW17047P-PA-GF50	Black
Mercedes-Benz	DBL5408.55 (PA66+PA6) - GF50	
Mercedes-Benz	DBL5409.35 PA66 GF50	
Stellantis	B62 0300 / 61/222E/219M/H115	CPN5139;01378_21_02459

Zytel® PLS95G50DH2 BK261

ZYTEL® PLUS & XT NYLON RESIN

Stellantis - Chrysler	MS.50017 / CPN-5139	Black
VW Group	VW 50133 PA66-8-A	
VW Group	VW 50133 PA66-8-A	
Valeo	PDTNVC15006 RevE	PA66/6T-GF50 Class 5A
Valeo	PDTNVC15006 RevE	PA66/6T-GF50 Class 6
Valeo	PDTNVC15006 RevE	PA66/6T-GF50 Class 5B


Characteristics

Processing	Injection Molding
Additives	Release agent
Special characteristics	Heat stabilized or stable to heat

Zytel® PLS95G50DH2 BK261

ZYTEL® PLUS & XT NYLON RESIN


Dynamic Tensile modulus-temperature (dry)



Zytel® PLS95G50DH2 BK261

ZYTEL® PLUS & XT NYLON RESIN


Stress-strain (dry)



Zytel® PLS95G50DH2 BK261

ZYTEL® PLUS & XT NYLON RESIN


Stress-strain (cond.)



Zytel® PLS95G50DH2 BK261

ZYTEL® PLUS & XT NYLON RESIN


Secant modulus-strain (dry)



Zytel® PLS95G50DH2 BK261

ZYTEL® PLUS & XT NYLON RESIN


Secant modulus-strain (cond.)



Zytel® PLS95G50DH2 BK261

ZYTEL® PLUS & XT NYLON RESIN


Stress-strain (isochronous) 73.4 °F (cond.)



Zytel® PLS95G50DH2 BK261

ZYTEL® PLUS & XT NYLON RESIN


Creep modulus-time 73.4 °F (cond.)



Zytel® PLS95G50DH2 BK261

ZYTEL® PLUS & XT NYLON RESIN


Stress-strain (isochronous) 212°F (dry)



Zytel® PLS95G50DH2 BK261

ZYTEL® PLUS & XT NYLON RESIN


Creep modulus-time 212°F (dry)



Zytel® PLS95G50DH2 BK261

ZYTEL® PLUS & XT NYLON RESIN


Stress-strain (isochronous) 392 °F (dry)



Zytel® PLS95G50DH2 BK261

ZYTEL® PLUS & XT NYLON RESIN


Creep modulus-time 392°F (dry)



Zytel® PLS95G50DH2 BK261

ZYTEL® PLUS & XT NYLON RESIN


Tensile modulus-temperature (dry)



Zytel® PLS95G50DH2 BK261

ZYTEL® PLUS & XT NYLON RESIN


Tensile modulus-temperature (cond.)



Zytel® PLS95G50DH2 BK261

ZYTEL® PLUS & XT NYLON RESIN

Tensile Fatigue, 10Hz, R=0.1 @ 0.08in (dry)



Zytel® PLS95G50DH2 BK261

ZYTEL® PLUS & XT NYLON RESIN

Chemical Media Resistance

Acids

- ✔ Acetic Acid (5% by mass), 23°C
- ✔ Citric Acid solution (10% by mass), 23°C
- ✔ Lactic Acid (10% by mass), 23°C

Mineral oils

- ✔ SAE 10W40 multigrade motor oil, 23°C
- ✔ SAE 10W40 multigrade motor oil, 130°C
- ✔ SAE 80/90 hypoid-gear oil, 130°C
- ✔ Insulating Oil, 23°C
- ✔ Motor oil OS206 304 Ref.Eng.Oil, ISP, 135°C
- ✔ Automatic hypoid-gear oil Shell Donax TX, 135°C
- ✔ Hydraulic oil Pentosin CHF 202, 125°C

Other

- ✔ Ethylene Glycol (50% by mass) in water, 108°C
- ✘ Water, 90°C
- ✔ Coolant Glysantin G48, 1:1 in water, 125°C

Symbols used:

✔ possibly resistant
Defined as: Supplier has sufficient indication that contact with chemical can be potentially accepted under the intended use conditions and expected service life. Criteria for assessment have to be indicated (e.g. surface aspect, volume change, property change).

✘ not recommended - see explanation
Defined as: Not recommended for general use. However, short-term exposure under certain restricted conditions could be acceptable (e.g. fast cleaning with thorough rinsing, spills, wiping, vapor exposure).

Revised: 2026-08-12 Source: Celanese Materials Database

NOTICE TO USERS: Values shown are based on testing of laboratory test specimens and represent data that fall within the standard range of properties for natural material. These values alone do not represent a sufficient basis for any part design and are not intended for use in establishing maximum, minimum, or ranges of values for specification purposes. Colorants or other additives may cause significant variations in data values. Properties of molded parts can be influenced by a wide variety of factors including, but not limited to, material selection, additives, part design, processing conditions and environmental exposure. Other than those products expressly identified as medical grade (including by MT® product designation or otherwise), Celanese's products are not intended for use in medical or dental implants. Regardless of any such product designation, any determination of the suitability of a particular material and part design for any use contemplated by the users and the manner of such use is the sole responsibility of the users, who must assure themselves that the material as subsequently processed meets the needs of their particular product or use. To the best of our knowledge, the information contained in this publication is accurate; however, we do not assume any liability whatsoever for the accuracy and completeness of such information. The information contained in this publication should not be construed as a promise or guarantee of specific properties of our products. It is the sole responsibility of the users to investigate whether any existing patents are infringed by the use of the materials mentioned in this publication. Moreover, there is a need to reduce human exposure to many materials to the lowest practical limits in view of possible adverse effects. To the extent that any hazards may have been mentioned in this publication, we neither suggest nor guarantee that such hazards are the only ones that exist. We recommend that persons intending to rely on any recommendation or to use any equipment, processing technique or material mentioned in this publication should satisfy themselves that they can meet all applicable safety and health standards. We strongly recommend that users seek and adhere to the manufacturer's current instructions for handling each material they use, and entrust the handling of such material to adequately trained personnel only. Please call the telephone numbers listed for additional technical information. Call Customer Services for the appropriate Materials Safety Data Sheets (MSDS) before attempting to process our products.
Copyright © 2026 Celanese or its affiliates. All rights reserved.
Celanese®, registered C-ball design and all other trademarks identified herein with ®, TM, SM, unless otherwise noted, are trademarks of Celanese or its affiliates.