Zytel® XT70G35HSL BK044A

ZYTEL® PLUS & XT NYLON RESIN

Common features of Zytel® nylon resin include mechanical and physical properties such as high mechanical strength, excellent balance of stiffness and toughness, good high temperature performance, good electrical and flammability properties, good abrasion and chemical resistance. In addition, Zytel® nylon resins are available in different modified and reinforced grades to create a wide range of products with tailored properties for specific processes and end-uses. Zytel® nylon resin, including most flame retardant grades, offer the ability to be coloured.

The good melt stability of Zytel® nylon resin normally enables the recycling of properly handled production waste. If recycling is not possible, we recommend, as the preferred option, incineration with energy recovery (-31kJ/g of base polymer) in appropriately equipped installations. For disposal, local regulations have to be observed.

Zytel® nylon resin typically is used in demanding applications in the automotive, furniture, domestic appliances, sporting goods and construction industry.

Zytel® XT70G35HSL BK044A is a 35% glass fiber reinforced, heat stabilized polyamide 66 resin for injection molding. It has been developed for automotive applications requiring good retention of properties over time at temperatures up to 220 °C and with good high temperature fatigue and properties.

Product information

Resin Identification	PA66-GF35	ISO 1043
Part Marking Code	>PA66-GF35<	ISO 11469
ISO designation	ISO 16396-PA66,GF35,M1CGHR,S14-110	

Rheological properties

	dry/cond.		
Viscosity number	3880[1]/*	in³/lb	ISO 307, 1628
Molding shrinkage, parallel	0.3 / -	%	ISO 294-4, 2577
Molding shrinkage, normal	0.9 / -	%	ISO 294-4, 2577

[1]: sulfuric acid 96% (130 cm³/g in formic acid 90%)

Typical mechanical properties

	dry/cond.		
Tensile modulus	1.6E6 / 1.09E6	psi	ISO 527-1/-2
Tensile stress at break, 5mm/min	29000 / 20300	psi	ISO 527-1/-2
Tensile strain at break, 5mm/min	3.2 / 5	%	ISO 527-1/-2
Flexural modulus	1.45E6 / 1.02E6	psi	ISO 178
Flexural strength	37700 / -	psi	ISO 178
Charpy impact strength, 23 °C	42.8 / 47.6	ftlb/in²	ISO 179/1eU
Charpy impact strength, -30 °C	38.1 / -	ftlb/in²	ISO 179/1eU
Charpy notched impact strength, 23 °C	6.18 / 7.61	ftlb/in²	ISO 179/1eA
Charpy notched impact strength, -40 °C	5.23 / 4.76	ftlb/in²	ISO 179/1eA

Thermal properties

	dry/cond.		
Melting temperature, 10 °C/min	496 / *	°F	ISO 11357-1/-3
Glass transition temperature, 10 °C/min	149 / 68	°F	ISO 11357-1/-3
Temperature of deflection under load, 1.8 MPa	464 / *	°F	ISO 75-1/-2
Coefficient of linear thermal expansion (CLTE), parallel	0.11 / *	E-4/°F	ISO 11359-1/-2
Coefficient of linear thermal expansion (CLTE), Parallel, 23-55 °C(73-130 °F)	0.111 / -	E-4/°F	ASTM E 831

Zytel® XT70G35HSL BK044A

ZYTEL® PLUS & XT NYLON RESIN

Coefficient of linear thermal expansion (CLTE), parallel, -40-23°C	0.106 / *	E-4/°F	ISO 11359-1/-2
Coefficient of linear thermal expansion (CLTE), parallel, 55-160°C	0.0833 / *	E-4/°F	ISO 11359-1/-2
Coefficient of linear thermal expansion (CLTE), normal	0.5 / *	E-4/°F	ISO 11359-1/-2
Coefficient of linear thermal expansion (CLTE), Normal,23-55°C (73-130°F)	0.389 / -	E-4/°F	ASTM E 831
Coefficient of linear thermal expansion (CLTE), normal, -40-23°C	0.306 / *	E-4/°F	ISO 11359-1/-2
Coefficient of linear thermal expansion (CLTE), normal, 55-160°C	0.833 / *	E-4/°F	ISO 11359-1/-2
Thermal conductivity of melt	0.25	W/(m K)	ISO 22007-2
Specific heat capacity of melt	2050	J/(kg K)	ISO 22007-4

Flammability

FMVSS Class	B		ISO 3795 (FMVSS 302)
Burning rate, Thickness 1 mm	1.3	in/min	ISO 3795 (FMVSS 302)

Electrical properties

	dry/cond.		
Electric strength	889 / 406	kV/in	IEC 60243-1

Physical/Other properties

	dry/cond.		
Humidity absorption, 2mm	2.1 / *	%	Sim. to ISO 62
Density	0.0509 / -	lb/in³	ISO 1183
Density of melt	77.4	lb/ft³	

Emissions

Coeff. of linear therm. expansion -40°C to +100°C, parallel	19	E-6/K	ISO 11359-1/-2
Coeff. of linear therm. expansion -40°C to +100°C, normal	90	E-6/K	ISO 11359-1/-2

Injection

Drying Recommended	yes	
Drying Temperature	176	°F
Drying Time, Dehumidified Dryer	2 - 4	h
Processing Moisture Content	≤0.2	%
Melt Temperature Optimum	554	°F
Min. melt temperature	536	°F
Max. melt temperature	572	°F
Mold Temperature Optimum	203	°F
Min. mold temperature	158	°F
Max. mold temperature	248	°F
Hold Pressure Time (h is the max. wall thickness of the part in mm)	h²+2	s
Ejection temperature	412	°F

Zytel® XT70G35HSL BK044A

ZYTEL® PLUS & XT NYLON RESIN

Automotive

OEM	STANDARD	ADDITIONAL INFORMATION
BMW	GS93016-PA66-GF35	(Highly Heat Aging Resistant)
General Motors	GMW17961P-PA-GF35-T2	Black
Hyundai	MS211-72 Type B	
Hyundai	MS211-72 Type B	
Mercedes-Benz	DBL5408.50 PA66 GF35	
Renault-Nissan	AS23-b, No Spec, Special Part Approval, See Your CE Account Manager.	
Renault-Nissan	AS24, No Spec, Special Part Approval, See Your CE Account Manager.	
Renault-Nissan	AS24-a, No Spec, Special Part Approval, See Your CE Account Manager.	
Renault-Nissan	UB02a, No Spec, Special Part Approval, See Your CE Account Manager.	
Renault-Nissan	UB02d, No Spec, Special Part Approval, See Your CE Account Manager.	
Stellantis	B62 0300 / 61/219M-/221E/11/H114/H412 + S620001 (3000h/190°)	CPN5077;01994_15_00257
Stellantis - Chrysler	MS.50017 / CPN-5077	Black
VW Group	VW 50133 PA66-7-A	
Valeo	PDTNVC15006 RevE	PA66-GF35 Class 5A
Valeo	PDTNVC15006 RevE	PA66-GF35 Class 6

Characteristics

Processing	Injection Molding
Additives	Release agent
Special characteristics	Heat stabilized or stable to heat


Additional information

Injection molding

Zytel® XT70G35HSL BK044A

ZYTEL® PLUS & XT NYLON RESIN


Viscosity-shear rate



Zytel® XT70G35HSL BK044A

ZYTEL® PLUS & XT NYLON RESIN


Shearstress-shear rate



Zytel® XT70G35HSL BK044A

ZYTEL® PLUS & XT NYLON RESIN


Dynamic Shear modulus-temperature (dry)



Zytel® XT70G35HSL BK044A

ZYTEL® PLUS & XT NYLON RESIN


Dynamic Tensile modulus-temperature (dry)



Zytel® XT70G35HSL BK044A

ZYTEL® PLUS & XT NYLON RESIN


Stress-strain (dry)



Zytel® XT70G35HSL BK044A

ZYTEL® PLUS & XT NYLON RESIN


Stress-strain (cond.)



Zytel® XT70G35HSL BK044A

ZYTEL® PLUS & XT NYLON RESIN

Secant modulus-strain (dry)




Revised: 2026-08-12 Source: Celanese Materials Database

Zytel® XT70G35HSL BK044A

ZYTEL® PLUS & XT NYLON RESIN


Secant modulus-strain (cond.)



Zytel® XT70G35HSL BK044A

ZYTEL® PLUS & XT NYLON RESIN


Stress-strain (isochronous) 320 °F (dry)



Zytel® XT70G35HSL BK044A

ZYTEL® PLUS & XT NYLON RESIN


Creep modulus-time 320 °F (dry)



Zytel® XT70G35HSL BK044A

ZYTEL® PLUS & XT NYLON RESIN


Stress-strain (isochronous) 374 °F (dry)



Zytel® XT70G35HSL BK044A

ZYTEL® PLUS & XT NYLON RESIN


Creep modulus-time 374 °F (dry)



Zytel® XT70G35HSL BK044A

ZYTEL® PLUS & XT NYLON RESIN


Stress-strain (isochronous) 392 °F (dry)



Zytel® XT70G35HSL BK044A

ZYTEL® PLUS & XT NYLON RESIN


Creep modulus-time 392°F (dry)



Zytel® XT70G35HSL BK044A

ZYTEL® PLUS & XT NYLON RESIN


Tensile modulus-temperature (dry)



Zytel® XT70G35HSL BK044A

ZYTEL® PLUS & XT NYLON RESIN


Tensile modulus-temperature (cond.)



Zytel® XT70G35HSL BK044A

ZYTEL® PLUS & XT NYLON RESIN

Tensile Fatigue, 10Hz, R=0.1 @ 0.08in (dry)



Zytel® XT70G35HSL BK044A

ZYTEL® PLUS & XT NYLON RESIN

Chemical Media Resistance

Acids

- ✔ Acetic Acid (5% by mass), 23°C
- ✔ Citric Acid solution (10% by mass), 23°C
- ✔ Lactic Acid (10% by mass), 23°C
- ✘ Hydrochloric Acid (36% by mass), 23°C
- ✘ Nitric Acid (40% by mass), 23°C
- ✘ Sulfuric Acid (38% by mass), 23°C
- ✘ Sulfuric Acid (5% by mass), 23°C
- ✘ Chromic Acid solution (40% by mass), 23°C

Bases

- ✘ Sodium Hydroxide solution (35% by mass), 23°C
- ✔ Sodium Hydroxide solution (1% by mass), 23°C
- ✔ Ammonium Hydroxide solution (10% by mass), 23°C

Alcohols

- ✔ Isopropyl alcohol, 23°C
- ✔ Methanol, 23°C
- ✔ Ethanol, 23°C

Hydrocarbons

- ✔ n-Hexane, 23°C
- ✔ Toluene, 23°C
- ✔ iso-Octane, 23°C

Ketones

- ✔ Acetone, 23°C

Ethers

- ✔ Diethyl ether, 23°C

Mineral oils

- ✔ SAE 10W40 multigrade motor oil, 23°C
- ✔ SAE 10W40 multigrade motor oil, 130°C
- ✔ SAE 80/90 hypoid-gear oil, 130°C
- ✔ Insulating Oil, 23°C
- ✔ Motor oil OS206 304 Ref.Eng.Oil, ISP, 135°C
- ✔ Automatic hypoid-gear oil Shell Donax TX, 135°C
- ✔ Hydraulic oil Pentosin CHF 202, 125°C

Standard Fuels

- ✔ ISO 1817 Liquid 1 - E5, 60°C
- ✔ ISO 1817 Liquid 2 - M15E4, 60°C
- ✔ ISO 1817 Liquid 3 - M3E7, 60°C
- ✔ ISO 1817 Liquid 4 - M15, 60°C
- ✔ Standard fuel without alcohol (pref. ISO 1817 Liquid C), 23°C
- ✔ Standard fuel with alcohol (pref. ISO 1817 Liquid 4), 23°C
- ✔ Diesel fuel (pref. ISO 1817 Liquid F), 23°C
- ✘ Diesel fuel (pref. ISO 1817 Liquid F), 90°C
- ✘ Diesel fuel (pref. ISO 1817 Liquid F), >90°C

Zytel® XT70G35HSL BK044A

ZYTEL® PLUS & XT NYLON RESIN

Salt solutions

- ✔ Sodium Chloride solution (10% by mass), 23°C
- ✘ Sodium Hypochlorite solution (10% by mass), 23°C
- ✔ Sodium Carbonate solution (20% by mass), 23°C
- ✔ Sodium Carbonate solution (2% by mass), 23°C
- ✘ Zinc Chloride solution (50% by mass), 23°C

Other

- ✔ Ethyl Acetate, 23°C
- ✘ Hydrogen peroxide, 23°C
- ✔ DOT No. 4 Brake fluid, 130°C
- ✔ Ethylene Glycol (50% by mass) in water, 108°C
- ✔ 1% nonylphenoxy-polyethyleneoxy ethanol in water, 23°C
- ✔ 50% Oleic acid + 50% Olive Oil, 23°C
- ✔ Water, 23°C
- ✘ Water, 90°C
- ✘ Phenol solution (5% by mass), 23°C
- ✘ Coolant Glysantin G48, 1:1 in water, 125°C

Symbols used:

✔ possibly resistant
Defined as: Supplier has sufficient indication that contact with chemical can be potentially accepted under the intended use conditions and expected service life. Criteria for assessment have to be indicated (e.g. surface aspect, volume change, property change).

✘ not recommended - see explanation
Defined as: Not recommended for general use. However, short-term exposure under certain restricted conditions could be acceptable (e.g. fast cleaning with thorough rinsing, spills, wiping, vapor exposure).

NOTICE TO USERS: Values shown are based on testing of laboratory test specimens and represent data that fall within the standard range of properties for natural material. These values alone do not represent a sufficient basis for any part design and are not intended for use in establishing maximum, minimum, or ranges of values for specification purposes. Colorants or other additives may cause significant variations in data values. Properties of molded parts can be influenced by a wide variety of factors including, but not limited to, material selection, additives, part design, processing conditions and environmental exposure. Other than those products expressly identified as medical grade (including by MT® product designation or otherwise), Celanese's products are not intended for use in medical or dental implants. Regardless of any such product designation, any determination of the suitability of a particular material and part design for any use contemplated by the users and the manner of such use is the sole responsibility of the users, who must assure themselves that the material as subsequently processed meets the needs of their particular product or use. To the best of our knowledge, the information contained in this publication is accurate; however, we do not assume any liability whatsoever for the accuracy and completeness of such information. The information contained in this publication should not be construed as a promise or guarantee of specific properties of our products. It is the sole responsibility of the users to investigate whether any existing patents are infringed by the use of the materials mentioned in this publication. Moreover, there is a need to reduce human exposure to many materials to the lowest practical limits in view of possible adverse effects. To the extent that any hazards may have been mentioned in this publication, we neither suggest nor guarantee that such hazards are the only ones that exist. We recommend that persons intending to rely on any recommendation or to use any equipment, processing technique or material mentioned in this publication should satisfy themselves that they can meet all applicable safety and health standards. We strongly recommend that users seek and adhere to the manufacturer's current instructions for handling each material they use, and entrust the handling of such material to adequately trained personnel only. Please call the telephone numbers listed for additional technical information. Call Customer Services for the appropriate Materials Safety Data Sheets (MSDS) before attempting to process our products.
Copyright © 2026 Celanese or its affiliates. All rights reserved.
Celanese®, registered C-ball design and all other trademarks identified herein with ®, TM, SM, unless otherwise noted, are trademarks of Celanese or its affiliates.